



Asia Pacific Elite Corp.



2011.07.14 Design by Asia Pacific Elite Corp.



Tongtai Group
Asia Pacific Elite Corp.

No.26-3, Zhuangqian Rd., Shengang Dist., Taichung City 429, Taiwan (R.O.C.)
TEL : 886-4-25631959 FAX : 886-4-25631985 <http://www.apecnc.com>





**GM series Five-axis
High speed gantry type machining center**

Specification	Unit	GM22/GM27/GM32
Table	mm	(2500,3000,3500) × (4300,5300,6300)
X/Y/Z-axis Stroke	mm	(4000-30000)/(2200-3200)/1000
Rapid Traverser	m/min	50
Max. Acceleration	m/sec ²	5
Spindle Nose		HSK 63A
Spindle Speed	rpm	24000
Spindle Motor (Max.)	kw	42
Tool Capacity	pc	30(40,50)



**GF series Five-axis
Gantry type machining center**

Specification	Unit	GF35/GF40/GF45/GF50	
Table	mm	5000-30000 × 3500,4000,4500,5000	
X/Y/Z-axis Stroke	mm	5000-30000/3500,4000,4500,5000/1000,1300,1500	
X/Y/Z-axis Rapid Traverser	m/min	40	40
Max. Acceleration	m/sec ²	4	4
Spindle Nose		HSK 63A	HSK 100A
Spindle Speed	rpm	24000	12000
Spindle Motor (Max.)	kw	42	56
Tool Capacity	pc	40	40



**GL series
High speed gantry type machining center**

Specification	Unit	GL22/GL27/GL32
Table	mm	(2500,3000,3500) × (4300,5300,6300)
X/Y/Z-axis Stroke	mm	(4000-40000)/(2200-3200)/1000
Rapid Traverser	m/min	50
Max. Acceleration	m/sec ²	5
Spindle Nose		HSK 100A
Spindle Speed	rpm	15000
Spindle Motor (Max.)	kw	34
Tool Capacity	pc	20(30,40)



**MT series
Double column machining center**

Specification	Unit	MT19/MT23/MT27
Table	mm	2200-5200 × 1700
X/Y/Z-axis Stroke	mm	(2200-5200)/(1900-2700)/800(1070)
X/Y/Z-axis Rapid Traverser	m/min	12
Spindle Nose		BT50(BBT50)
Spindle Speed	rpm	6000
Spindle Motor (Max.)	kw	26
Tool Capacity	pc	40